

The **BUZZ** ground-mounted luminaire is engineered for exceptional light control and durability. Offering four distinct light distribution options, it delivers a wide beam of light from a low mounting height, making it ideal for ground-level illumination. Its impressive lighting quality is free from glare at normal viewing angles, enhancing visual comfort in outdoor spaces. **BUZZ** is available in two sizes and is powered by advanced COB LED technology, ensuring high efficiency and long-lasting performance.

Constructed from robust LM6 aluminum alloy with a clear polycarbonate cover, **BUZZ** is designed to withstand harsh environments. The luminaire is protected against dust, water, and potential impact, making it suitable for outdoor installations. The housing is double-coated with durable powder and nano-ceramic surface conversion, offering enhanced corrosion resistance and durability. Additionally, the luminaire is anti-humidity sealed and equipped with a pre-wired cable for easy, hassle-free installation.

Perfectly suited for walkways and pathways in both private and public settings, **BUZZ** provides effective visual guidance while maintaining architectural harmony. Its glare-free illumination improves safety and comfort in high-traffic areas. The anchorage unit for concrete foundation installation is available as an accessory, adding to its versatility in various lighting applications. Whether in residential complexes, parks, or commercial spaces, **BUZZ** is a reliable choice for superior ground lighting.



NEW! BUZZ4



NEW! Mini BUZZ4



www.unilamp.co.th/en/p/buzz

Specification

- Designed, manufactured and tested according to IEC 60598.
- LM6 die cast aluminum body.
- Stainless steel screws.
- Nano ceramic surface conversion.
- Double layer coating.
- Polycarbonate protective cover.
- Post-cured silicone gasket.
- High quality LED module and driver.
- Pre-wired cable from the factory.
- Installation must be carried out according to the enclosed product manual.

Available Color



****Custom colors are available on request.**

Mini BUZZ



1. Reflector

State of art high efficiency computer-aided design reflector.

2. LED Module

COB LED directly attached to the body for fastest heat transfer. 2700K, 3000K and 4000K CRI>80 3-Step SDCM.

3. Body Housing

Enhanced LM6 die-cast aluminum housing with 16-step coating process including nano ceramic film. Low copper content <0.1%

4. Cover.

Self-extinguishing PC protective cover. Protect against UV rays and mechanical impact.

Courtyard by Marriott, Aravali Resort, NCR, Delhi – INDIA



BUZZ

CE

TÜV
1195-2001



IK⁰⁸₀₇ OR IK⁰⁸₁₀

IP66 OR IP67







CRI >80

3 SDCM

UniShield16

UniBlock





Mini BUZZ1

Mini BUZZ2

Mini BUZZ3

Mini BUZZ4

NEW!






BUZZ1

BUZZ2

BUZZ3

BUZZ4

NEW!



BUZZ

Application Type : On-ground
Subgroup : Ground washer

Mini BUZZ1 / 7163

Mini BUZZ2 / 7164

Mini BUZZ3 / 7165

Mini BUZZ4 / 7167

BUZZ1 / 7160

BUZZ2 / 7161

BUZZ3 / 7162

BUZZ4 / 7166

New!

New!

Luminaire Performance

500 – 2970 lm

14 – 40 W

30 – 80 lm/W

Beam Options



Color Temperature

2700K/ 3000K/ 4000K

Controller

On-Off/ 1-10V/ DALI/ CASAMBI

On-Off [AC LED]

Input Options

220-240Vac 50/60Hz

Accessories



Anchor bolt



IP68 Connector

	Product Code	Luminaire Wattage	Beam	CCT	Luminaire Lumen	Efficacy	Controller					Ordering Code
											CASAMBI	
Mini BUZZ1	OD-7163	14 W	N/A	2700 K	1020 lm	72 lm/W	•					7163-0-3-503-XX 7163-0-3-901-XX 7163-0-3-904-XX
				3000 K	1080 lm	77 lm/W	•					
				4000 K	1130 lm	80 lm/W	•					
Mini BUZZ2	OD-7164	14 W	N/A	2700 K	520 lm	37 lm/W	•					7164-0-3-503-XX 7164-0-3-901-XX 7164-0-3-904-XX
				3000 K	550 lm	39 lm/W	•					
				4000 K	570 lm	40 lm/W	•					
Mini BUZZ3	OD-7165	14 W	N/A	3000 K	530 lm	37 lm/W	•					7165-0-3-901-XX
												
Mini BUZZ4	OD-7167	16 W	N/A	2700 K	500 lm	31 lm/W	•					7167-0-3-503-XX 7167-0-3-901-XX 7167-0-3-904-XX
				3000 K	530 lm	33 lm/W	•					
				4000 K	550 lm	34 lm/W	•					
				2700 K	500 lm	31 lm/W			•			7167-0-4-503-XX 7167-0-4-901-XX 7167-0-4-904-XX
				3000 K	530 lm	33 lm/W			•			
				4000 K	550 lm	34 lm/W			•			
				2700 K	500 lm	31 lm/W				•		7167-0-5-503-XX 7167-0-5-901-XX 7167-0-5-904-XX
				3000 K	530 lm	33 lm/W				•		
				4000 K	550 lm	34 lm/W				•		
				2700 K	500 lm	31 lm/W					•	7167-0-A-503-XX 7167-0-A-901-XX 7167-0-A-904-XX
				3000 K	530 lm	33 lm/W					•	
				4000 K	550 lm	34 lm/W					•	
BUZZ1	OD-7160	20 W	N/A	3000 K	1110 lm	55 lm/W		•				7160-0-3-873-XX 7160-0-3-887-XX 7160-0-3-891-XX 7160-0-3-877-XX 7160-0-3-902-XX
		27 W	N/A	3000 K	2040 lm	75 lm/W	•					
		4000 K		2100 lm	77 lm/W	•						
		30 W	N/A	3000 K	1670 lm	55 lm/W		•				
BUZZ2	OD-7161	20 W	N/A	3000 K	600 lm	30 lm/W		•				7161-0-3-873-XX 7161-0-3-887-XX 7161-0-3-891-XX 7161-0-3-902-XX
		27 W	N/A	3000 K	1100 lm	40 lm/W	•					
		40 W	N/A	2700 K	1540 lm	38 lm/W	•					
				3000 K	1610 lm	40 lm/W	•					
BUZZ3	OD-7162	27 W	N/A	3000 K	1120 lm	41 lm/W	•					7162-0-3-887-XX
BUZZ4	OD-7166	20 W	N/A	3000 K	640 lm	32 lm/W		•				7166-0-3-873-XX 7166-0-3-874-XX
				4000 K	680 lm	34 lm/W		•				
		27 W	N/A	2700 K	1130 lm	41 lm/W	•					7166-0-3-506-XX 7166-0-3-887-XX 7166-0-3-891-XX
				3000 K	1180 lm	43 lm/W	•					
				4000 K	1210 lm	44 lm/W	•					
				2700 K	1130 lm	41 lm/W			•			
				3000 K	1180 lm	43 lm/W			•			7166-0-4-506-XX 7166-0-4-887-XX 7166-0-4-891-XX
				4000 K	1210 lm	44 lm/W			•			
				2700 K	1130 lm	41 lm/W				•		
				3000 K	1180 lm	43 lm/W				•		
				4000 K	1210 lm	44 lm/W				•		7166-0-5-506-XX 7166-0-5-887-XX 7166-0-5-891-XX
				2700 K	1130 lm	41 lm/W					•	
				3000 K	1180 lm	43 lm/W					•	
				4000 K	1210 lm	44 lm/W					•	
		30 W	N/A	3000 K	960 lm	32 lm/W		•				7166-0-3-877-XX 7166-0-3-878-XX
				4000 K	1020 lm	34 lm/W		•				
		40 W	N/A	2700 K	1640 lm	41 lm/W	•					7166-0-3-505-XX 7166-0-3-902-XX 7166-0-3-905-XX
				3000 K	1720 lm	43 lm/W	•					
				4000 K	1760 lm	44 lm/W	•					
				2700 K	1640 lm	41 lm/W					•	7166-0-A-505-XX 7166-0-A-902-XX 7166-0-A-905-XX
				3000 K	1720 lm	43 lm/W					•	
				4000 K	1760 lm	44 lm/W					•	

*Please contact sales team for special request.