





# LED Wall Pack Light


## Installation Instructions



Packing List		
Screws		4pcs
Expansion screws		4pcs
Waterproof connector		1pcs




### Physical Dimensions (Unit: mm/inch)




Product Specifications	15W	25W	35W
Input Voltage	100-277 VAC / 120-277 VAC / 100-240 VAC / 220-240 VAC (Subject to the input voltage on nameplate)		
Power Frequency	50 / 60 Hz		
Outlook Dimensions	292x293x97mm (11.50"x11.54"x3.82")		
Luminaire Net Weight	2.6±0.3kg (5.73±0.66Lbs)		
Working Temperature	-30°C to +50°C (-22°F to +122°F)		
Storing Temperature	-40°C to +70°C (-40°F to +158°F)		

# Installation


1. ✖




2. ✖





3. ✖




4. ✖




Unit: mm/inch







5. ✖






6. ✖



## 7. A.Cable Side Input





## B.Cable Back Input





## Instruction for Power & CCT Selectable

Please select a suitable power and CCT by the switch before installaion.




## Photocell (Optional)

### Photocell





8. ✖




1. Only to be installed outside arms reach.
2. Please make sure the wire cord not being pressed when closing the lid.
3. Make sure to lock rotation shaft at correct position.

9. ✖



10. ✖



### AC cords

L	brown	black
N	blue	white
⊕	yellow/green	green

### DIM cords

**Note: color for dim cords subject to the cable label on luminaire**



**Warning! do not wire dim cord to high voltage, or dim function will fail.**

### Reminder

#### We appreciate your purchase!

Please read the entire instruction manual before installation and keep it for future reference.

1. Please do not modify or dismantle the luminaire or replace accessories without confirming with the supplier first.
2. Please authorize only qualified personnel to install the lamp and ensure they follow the instruction manual. Any improper installation might cause falling, electric shock, fire, or other injury, damage or hazard.
3. Please disconnect power before installation or any maintenance of the lamp. Do not touch the power supply when the lamp is operating.
4. If the luminaire begins to smoke or emit odors, please disconnect power since fire or electric shock may occur. And ask qualified person to inspect and maintain the luminaire.
5. If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
6. The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.
7. We suggest you adding a separate surge protection device in distribution box to extend luminaire lifespan.

### Applications

1. The product is designed for building exteriors, courtyard, hotel lobby, conference rooms, corridor and auditoriums to entryways and similar applications. For other special applications, please consult your salesperson to confirm firstly.
2. Too much dust or oil accumulation on PC lens will stop the lighting emit and heat dissipation, it will change lighting distribution, and cause high heat inside to affect LED chips performance. For such environments, we suggest you to clean the luminaire regularly to ensure longer lifespan. Or you need to use product with glass cover and better heat performance instead.
3. The suggested mounting height of the luminaire is 2.5-6m.