

Kimbal 6 - Adjustable Recessed Downlight

Product Code: KA6P148F4CW

- Available in Fixed Recessed, Adjustable Recessed, Surface Mount, and Cable/Rod Suspended versions.
- Multiple Beam Options - Excellent space to mounting height ratios achievable.
- Sustainability features with fully recyclable chassis & plastic free packaging. Innovation with Patented Adjustable downlight locking mechanism.
- Product Description: Kimbal 6 Adjustable Recessed Downlight Performance 56W Flush Wide Beam 4000K Non Dimming Clear Lens White


Kimbal 6 Family



Configured Product - KA6P148F4CW



Photometrics



Selection

Series	Adjustable Recessed Downlight
CRI	P Series CRI 80+
Output	LED Driver 1400mA
CCT	4000K
Reflector	Wide Beam Flush
Control	Non Dimming
Lens	Clear Lens
ProSpec Option	Not Required
Seismic Restraint	Not Required
Colour	White

Technical

Current	1400mA
Power	55
Lumen Output	6459
Efficacy	117.436363636364
SDMC	3
R9 Value	15
Insulation Class	DO NOT COVER
IP Rating	IP65 (Below Ceiling)
IEC60598	Complies
AS/NZ60598	Complies
COI Compliance	No
Weight	Luminaire Body Weight: 980g Driver Weight: 250g
Lifetime	L90/B10 > 75,000
Beam Angle	70°
Dimming	No Dimming

Dimension

Dimension	160mm H x 165mm D (150mm dia cutout)
Ceiling Thickness	10-50 mm
Rod / Cable Length	N/A

Configure Here