


KF6 SERIES
FIXED RECESSED DOWNLIGHT



Flush Reflector



Recessed Reflector

Technical Data

- Cut Out

• Overall

• Height

• Suitable ceiling
- 150mm

165mm

148mm

10-50mm
- Weight - body

• Weight - driver

• LED life @ L90/B10

• AS/NZS60598 - parts 1&2
- 850g

250g

≥75000 Hrs

Complies
- IK10/IP65 anti-ligature lens option

• Wall wash option

• Emergency option

• Adaption plate 150-250mm
- K6-RAP/150

K6-RAP/250
- Ultra CRI 97, R9 98 option on request

• Tunable white 2700-6500K option on request

• DALI 8 Tunable White (250-900mA)

• Casambi (350-1050mA)

SERIES	CRI	OUTPUT	REFLECTOR	CCT	CONTROL	LENS	COLOUR
KF6 Fixed Recessed Downlight	P CRI 80 R9 15 3 SDCM	2 10W 250mA 1300lm 130lm/W (IC-4)	8F Wide Beam 70° Flush Reflector	3 3000K	BLANK Non Dim	BLANK No Lens 70° / 30° Beam UGR22, IP6X*	W White
	X CRI 90 R9 55 2 SDCM (Cyanosis compliant with 4000K)	3 14W 350mA 1800lm 129lm/W (IC-4)	8R Wide Beam 70° Recessed Reflector	35 3500K (CRI90 only)	D1 DALI (250-1400mA)	C Clear Lens 70° / 30° Beam UGR22, IP65*	B Black
	U CRI 97 R9 98 2 SDCM Cyanosis compliant with 4000K)	5 20W 500mA 2500lm 125lm/W (CA90)	4F Narrow Beam 30° Flush Reflector	4 4000K	D3 1-10V (250-1400mA)	D Diffusion Lens 100° Beam UGR22, IP65*	S Special
		7 27W 700mA 3500lm 130m/W (CA90)	4R Narrow Beam 30° Recessed Reflector		D4 Phase Cutting (180-1050mA)	P Prismatic Lens 55° Beam UGR16 / UGR19^, IP65*	
		9 35W 900mA 4300lm 123lm/W (CA90)			D5 04A: Switch (350-1400mA)	R Red Lens 70° / 30° Beam IP65*	
		10 40W 1050mA 5000lm 125lm/W (CA90)			D6 Push (250-1400mA)	G Green Lens 70° / 30° Beam IP65*	
		14 56W 1400mA 6500lm 116lm/W (Do Not Cover)			D7 04A: DALI (350-1400mA)	B Blue Lens 70° / 30° Beam IP65*	

*Downlight without lens is IP6X from below and above ceiling. Downlight with lens installed on site is IP54 from below and IP44 from above ceiling. Downlight with lens installed in factory is IP65 from below and IP44 from above ceiling. ^UGR16 capable with Recessed Reflector and Prismatic Lens, UGR19 capable with Flush Reflector and Prismatic Lens.


KF6 SERIES

Accessories



Wide Beam Reflector
70° Beam, UGR22, IP6X*

Narrow Beam Reflector
30° Beam, UGR22, IP6X*



Wide Beam Reflector + Clear Lens
70° Beam, UGR22, IP65*

Wide Beam Reflector + Diffusion Lens
100° Beam, UGR22, IP65*

Wide Beam Reflector + Prismatic Lens
55° Beam, UGR16 / UGR19^, IP65*



*Downlight without lens is IP6X from below and above ceiling. Downlight with lens installed on site is IP54 from below and IP44 from above ceiling. Downlight with lens installed in factory is IP65 from below and IP44 from above ceiling. ^UGR16 capable with Recessed Reflector and Prismatic Lens, UGR19 capable with Flush Reflector and Prismatic Lens.