

BLAZE

■ POLE MOUNTED



The **BLAZE** is an indirect light pole-top luminaire, designed to provide smooth and uniform light distribution across designated areas. The top reflector is adjustable, allowing for both symmetric and asymmetric light distribution, ensuring precise illumination for various applications while also minimizing glare. This flexibility makes **BLAZE** adaptable to different lighting needs, enhancing its performance in diverse outdoor environments.

Designed for mounting at heights between 3 to 5 meters, **BLAZE** is equipped with cutting-edge COB LED technology, available in 2700K, 3000K, and 4000K color temperatures, allowing it to create the perfect ambiance for different outdoor settings. Its advanced controller offers simple on-off functionality, 1-10V dimming, and DALI controllability, providing enhanced flexibility and energy efficiency in managing light output.

To ensure durability and performance in outdoor environments, **BLAZE** is equipped with a 10kV surge protector, safeguarding it from power fluctuations and prolonging the luminaire's lifespan.

For installation, **BLAZE** offers multiple options, including Aluminium poles, Galvanized steel poles, and a concrete anchorage unit, allowing for versatile and stable mounting solutions. With its robust design, advanced LED technology, and customizable features, **BLAZE** is the perfect choice for public spaces requiring reliable and visually appealing lighting solutions.



www.unilamp.co.th/en/p/blade

Specification

- Designed, manufactured and tested according to IEC 60598.
- LM6 die cast aluminum housing.
- Stainless steel screws.
- Nano ceramic surface conversion.
- Double layer coating.
- Safety glass cover.
- Post-cured silicone gasket.
- High quality LED module and driver.
- Pre-wired cable from the factory.
- Installation must be carried out according to the enclosed product manual.

Available Color



****Custom colors are available on request.**

Typical Application



BLAZE

CE

TUV



IK 08
06

IP65






CRI
>80

3
SDCM


UniShield16

BLAZE




BLAZE


Application Type : Pole mounted
Subgroup : Urban ambient

BLAZE / 7223	
Luminaire Performance	
4510 – 5670 lm	
57 W	
79 – 99 lm/W	
Beam Options	
	
Color Temperature	
2700K/ 3000K/ 4000K	
Controller	
On-Off/ DALI	
Input Options	
220–240Vac 50/60Hz	


Accessories






Aluminum pole



Steel pole



Anchor bolt

	Product Code	Luminaire Wattage	Beam	CCT	Luminaire Lumen	Efficacy	Controller		Ordering Code
									
BLAZE	OD-7223		N/A	2700 K	4510 lm	79 lm/W	• • •	•	7223-0-3-507-XX 7223-0-3-903-XX 7223-0-5-903-XX 7223-0-3-906-XX
				3000 K	5400 lm	94 lm/W			
				3000 K	5400 lm	94 lm/W			
				4000 K	5670 lm	99 lm/W			

**Please contact sales team for special request.*



City Land Mall - DUBAI