



ORNA

SPECIFICATIONS

RoHS

ZD

IP 66

IK 08

PRODUCT NAME	ORNA
HOUSING	Die-cast aluminium LED module
BOWL	Vertical: clear PMMA Horizontal: flat in clear polycarbonate
FINISH	Polyester powder coating, any colour available
SOURCES	ORALED / BLS strips/ backlighting
BACK LIGHTING	Bowl back-lighting: RGBW Optional diffusing film
COLOUR TEMPERATURE	ORALED: 2700 K, 3000 K or 4000 K (others on request) BLS: Amber*, 2200 K, 2400 K, 2700 K, 3000 K or 4000 K
OPTICAL	ORALENS or QUADRALENS
BACKLIGHT SHIELD	Medium or high as an option
FLUX & POWER**	Up to 10 096lm; 75W
ELECTRICAL CLASS	Class I or II
WIRING	Pre-wired at the factory
MOUNTING	Suspended

*Approx. 1800K

**At 3000K, in accordance with performance standards IEC 62717 and IEC 62722 (+/-5%tolerance)

DECORATIVE MOTIFS

BUBBLE

LACE

VENGA

Customised design option
(subject to study)

- ▶ Smart-ready® (Zd4i)

▶ Dimming

▶ Detection

▶ Tunable white options

▶ WIZARD management system (pag. 420)

MECHANICAL INTERFACES

